



# TECHNICAL SHEET

PRODUCT CODE

SAFETY SHOES

TSH-120

Features: 200J Steel toecap inside  
Steel mid-sole inside  
Anti-slip  
Anti-static  
Use: 2-layered Urethane Sole  
Reinforced toe by Leather (Acrylonitrile-Butadiene-Styrene resin)  
To protect feet of wearer  
Mining, Construction, Transportation, Warehouse etc.

Material: Upper : Polyurethane, Leather  
(Acrylonitrile-Butadiene-Styrene resin)  
Sole : Polyurethane  
Toecap : Steel  
Mid-sole : Steel

Color: Black  
Packing: 1 pair / Paper box  
10 pairs / Carton

Size	Length (mm)	Width (mm)	Weight (g)
35	255	96	1060
36	260	98	1080
37	265	100	1095
38	270	102	1110
39	275	104	1,125
40	280	106	1,140
41	285	108	1,155
42	295	110	1,170
43	300	112	1,185
44	305	114	1,200
45	310	116	1,215
47	320	120	1,245
49	330	124	1,275

Accordance with JIS	Compression Resistance (JIS T8101)	H
	Shock Resistance (JIS T8101)	H
	Antistatic Performance (JIS T8103)	ED
	Penetration Resistance (JIS T8101)	1,100N
	Water Resistance (JIS T8101)	-

Accordance with ISO 20345	Compression Resistance (ISO 20345)	15kN
	Shock Resistance (ISO 20345)	200J



Reinforced toe (Leather)

2-layered Urethane Sole

BOX



200J Steel Toe Cap

Steel mid-sole